

Product

June 2022

Silicon Additive RC260**Product description**

RC260 is a multifunctional silicone additive for UV curable inks and coatings. The acrylate functionality gives a permanent binding into the UV- matrix with long- lasting effects. It can be cured under atmospheric and nitrogen conditions. UV curing under nitrogen conditions improves the crosslinking significantly and gives excellent properties. The addition level depends on the application and the formulation used. Sufficient UV output and proper curing condition have a decisive influence for good results.

Features

- High release effect
- Moderate miscibility
- Improving flow and leveling
- High slip
- High mechanical resistance
- Addition levels: > 0,5%; levels are determined through laboratory tests.

- Acrylated PDMS
- Viscosity: 600 mPa.s
- Active substance: 100%

Precautions

Addition to inks and coatings as supplied. RC260 needs to be stirred well into the formulation. RC260 can be stored in a dry environment with temperature between 5 – 40 °C. The shelf life is 12 months from date of production. Close container immediately after usage

Background

The information is based on our experience. Because of the differences in materials for printing, processing conditions and test criteria this information can only be of an advisory nature. Our data reflect the latest state of our knowledge and are based on the characteristics established in the laboratory and on practical experience. Your own tests with the original materials under the respective conditions are indispensable. We disclaim any liability for applications for which this product is not foreseen. The user must determine under his own production conditions if the product meets his requirements.